



Waterborne Emulsified Linseed Oil Paint

DESCRIPTION & USE	Linseed Oil Emulsion (LOE) is a traditional decorative and protective coating used for plinths, barns, fences, sheds and all woodwork giving a water resistant, flexible coating, with high opacity, longevity and easy application. LOE also gives good adhesion to primed steel and old concrete.
COLOUR RANGE	Colour card & colour matching
FINISH	Matt
STORAGE	Between 5 & 25°C, 12 months in unopened containers.
DRYING TIME	Water resistant in 1 hour @ 20°C, 3-7 days for full drying, weather dependent
OVERCOATING TIME	24 hours
THEORETICAL SPREAD RATE	8m ² per litre per coat.
COATS	Recommended 3 coat system, (1 priming coat, 2 full coats)
PACK SIZE	2.5, 5 & 10 Litres
THINNER/CLEANER	Water
APPLICATION METHOD	Brush (recommended) or medium pile roller
SAFETY PRECAUTIONS	Application materials and soiled rags may self ignite without warning. Dispose of safely by laying flat and allowing to dry or clean with warm soapy water to avoid fire risks.

Information given is based upon formulations in use at time of printing. We reserve the right to modify any product without notice although in the case of any major modification a new data sheet will be issued.