



OIL EGGSHELL

TECHNICAL DATA SHEET

DESCRIPTION & USE	A tough, hard wearing, washable film. Low odour and excellent application properties. Excellent water resistance and durability.
COLOUR RANGE	White & colour matching
PERFORMANCE & USE	For all interior & exterior wood. Gives a low lustre finish.
FINISH	Eggshell
STORAGE/SHELF LIFE	Keep away from children. Keep away from heat/sparks/open flames 12 months minimum when kept in a tightly closed container and stored between 5 & 20°C
DRYING TIME	4-6 hours @ 20° depending on airflow and humidity.
OVERCOATING TIME	16 hours minimum
THEORETICAL SPREAD RATE	12m ² per litre per coat.
COATS	Apply 1 coat making sure to brush out well
PACK SIZE	2.5 Litres & 5 Litres
THINNER/CLEANER	Solvent
APPLICATION METHOD	Substrate temperature must exceed 5°C for applying and during drying. Adequate dry air ventilation should be applied during drying. By brush, roller & Airless spray.
IMPORTANT	Always refer to the Health & Safety sheet for the product before use and observe the warning phrases. In general avoid inhalation of spray mist and skin contact by the use of masks, gloves and other personal protection. Eyes should be copiously washed with water or proprietary wash and medical



attention obtained. Skin should be thoroughly washed using a cleanser or soap and water. Product is flammable.

Information given is based upon formulations in use at time of printing. We reserve the right to modify any product without notice although in the case of any major modification a new data sheet will be issued.