



PURE LINSEED OIL PAINT

TECHNICAL DATA SHEET

DESCRIPTION	Pure Linseed Oil Paint (PLOP) is a traditional original solvent free oil paint used as a decorative and protective coating for all woodwork giving a water resistant, flexible coating, with high opacity, excellent longevity and easy application. Highly pigmented in 100% Pale Boiled Linseed Oil, with added driers but NO solvent, using traditional and modern pigments.
PERFORMANCE	Provides a highly durable coat in a gloss finish.
COLOUR RANGE	White, Black & most colours by colour matching service (minimum 2.5 Litre order for new colour match)
FINISH	Gloss
STORAGE	12 months in unopened containers.
DRYING TIME	Very slow drying, up to two weeks for full drying, weather dependant.
OVERCOATING	24 hours MINIMUM
THEORETICAL	
SPREAD RATE	8m ² per litre per coat.
COATS	Minimum of 2 coats (Where application is on old bare timber, apply Linseed Oil as a primer/ sealer coat and wipe off any excess oil)
PACK SIZE	2.5 & 5 litres
THINNER	a) By adding Linseed Oil but this will reduce opacity slightly. b) An original thinning method was to stand the tin of paint in a container of very hot water. c) With solvent - preferably Genuine Turpentine but this does reduce the solids content and also introduces flammability. Solvent as a cleaner.