

### Description

The Traditional Paint Company Oil Based Eggshell is a tough, hard wearing, washable film. Low odour and excellent application properties. Excellent water resistance and durability.

For all interior & exterior wood. Gives a low lustre finish.

### Colour & Finish

Available in white & broad range of colours via tinting. Eggshell finish.

### Application

Apply 1 coat making sure to brush out well.

Substrate temperature must exceed 5°C for applying and during drying. Adequate dry air ventilation should be applied during drying. By brush, roller & Airless spray.

**IMPORTANT** Always refer to the Health & Safety sheet for the product before use and observe the warning phrases. In general avoid inhalation of spray mist and skin contact by the use of masks, gloves and other personal protection. Eyes should be copiously washed with water or proprietary wash and medical attention obtained. Skin should be thoroughly washed using a cleanser or soap and water. Product is flammable.

### Technical Data

- Drying Time: 4 - 6 hours at 20°C depending on airflow and humidity
- Overcoatable: 16 hours minimum at 20°C

### Coverage Rate

12m<sup>2</sup> per litre per coat.

### Thinner / Cleaner

Solvent.

### Shelf Life

12 months if stored in original unopened container at temperatures between 5 and 20°C.  
Keep away from children. Keep away from heat/sparks/open flames.

### Packaging

Available in 2.5 and 5 Litres.

Information given is based upon formulations in use at time of printing. We reserve the right to modify any product without notice although in the case of any major modification a new data sheet will be issued.